



BUILDERS CHOICE

Pave Rite – Modified Paving Sand (PR20)

DESCRIPTION

Builders Choice Pave Rite is a polymer modified paving-gap sand that is specifically designed to complement installed pavers around the house, pool areas and driveways. It is also suitable for commercial paving applications. PAVE RITE sets rigid to inhibit weed growth, insect penetration and erosion. It will also resist scouring caused by sweeping, water rinsing and traffic.



COMPOSITION

Builders Choice PAVE RITE is a blended mixture of premium washed paving sand, polymeric additives and proprietary additives. When activated (by water), Pave Rite forms a firm barrier; providing a stable fill-in joint between the pavers.

PAVE RITE INSTALLATION

PAVE RITE, whilst easy to use, requires a few basic steps to prevent unnecessary clean up and extra work. To create long lasting paving joints around your home, business or commercial paving job use PAVE RITE between the paving joints for maintenance free enjoyment for years. Our blend of quality ingredients have been polymer modified to provide insect and weed control capabilities to deliver a long lasting and superior solution to next paving project.

INSTALLATION PREPARATION

1. Spread Builders Choice PAVE RITE evenly over dry pavers and sweep into paving joints with a suitable broom. For best results fill joints to approximately 3mm below the top.
2. If necessary use a compactor.
3. If needed, spread a further layer of PAVE RITE and repeat.
4. Sweep off all extra sand and residues to provide a clean paver surface to ensure the pavers surfaces is completely free from sand and dust.
5. Wet the entire area with a fine mist spray. Thoroughly saturate but not flood the area. This can be done in stages to ensure the water seeps through the Gap Sand joint areas. This should be done on a sunny day.
6. **DO NOT** use a high pressure water jet.
7. Allow PAVE RITE to cure through drying.
8. Optimum gap between pavers is between 2 and 5mm.


CURING AND MAINTENANCE

The area should remain traffic free for a long as possible following the application of PAVE RITE. Avoid using PAVE RITE in areas which is constantly wet. The drying out of PAVE RITE occurs fastest on top and slower at the bottom. The entire joint may take a number of weeks to fully dry and bond depending on conditions. If an area needs additional sand replenishment simply follow the steps above.

SAFETY & HANDLING

Wear a dust mask, goggles and gloves whilst using this product. If the product comes into contact with your eyes, flush thoroughly and repeatedly with water. **DO NOT RUB EYES.** Wash hands after use. Do not take internally.

Typical Properties

Yield per 20kg bag (depending on size and shape of paver)	Approximately 4m ² per 20kg bag at 3mm gap width
Sand Grading	A suitably finely graded, high quality, clean, West Australian sand is used in this Product.
Set Characteristics	The PAVE RITE is flexible to rigid with good bonding to paver edge to minimise weed growth and repel insects.
Curing Time	This depends upon climate, ambient temperature and gap required between pavers.
Packaging	20kg sacks
Package Recycling	
Storage	Indefinite in dry place

The end-use of this product is beyond the manufacturer's control, and liability is restricted to the replacement of material proven to be faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage of this product.

The information contained herein is provided in good faith and to the best of our knowledge is true and accurate. No warranty is implied or given as to its completeness or accuracy in describing the performance or suitability of the product for a particular application. Users are requested to check that the literature in their possession is of the latest issue.

BUILDERS CHOICE is a registered trade mark of BGC (Australia) Pty Ltd t/a BGC Cement.

BGC Cement
BGC (Australia) Pty Ltd
ABN 62 005 736 005 007

77 Vulcan Road Canning Vale
Western Australia 6155
PO Box 1408 Canning Vale WA 6970
Telephone (08) 9334 4555
Facsimile (08) 9334 4544
Email: cement@bgc.com.au
Website: www.builderschoice.com.au